



CC PWP

Integral Waterproofing Admixture in Powder Form.

DESCRIPTION

CC PWP is a waterproofing admixture in powder form, designed for use in all cement-based applications, such as:

- plastering and rendering exposed to rain
- mounting mortar
- joint grout
- screed
- concrete

It minimises penetration of moisture into the mortar. It improves the workability of fresh mortar, plaster, or concrete.

INSTRUCTIONS FOR USE

CC PWP is dosed for 1 kg of 50 kg cement: • Spread the 1-kg over cement and aggregates. Usual mixture proportions shall be respected.

Example :
for mortar: 1 part of cement for 3 parts of clean and selected sand. Do not pre-dissolve it in the mixing water.

- Add the quantity of water required and mix well.
- Apply your mortar on a well-prepared substrate: clean, free from dust and all traces of oil or laitance. Few hours before apply, dampen the support.
- Cure and protect the mortar as usual.

CHARACTERISTICS

Appearance White Powder
Specific Gravity 0.8
Cl- Content Nil
Solubility Partial in Water

PACKAGING

CC PWP is supplied in 5 kg and 10 Kg plastic bag.



STORAGE

12 months from manufacturing date, in dry conditions and original packaging.

CAUTIONS HEALTH AND SAFETY

Avoid prolonged contact with skin. Wear protective gear for hands & eyes. Splashes on the skin should be washed away by cleaning with soap and water. In case of contact with eyes, wash thoroughly with clean water. If swallowed, do not induce vomiting, in both cases seek medical attention

FIRE

CC PWP is nonflammable.