



CC WSS10

Solvent based sealer Waterproofing Membrane

DESCRIPTION

CC WSS10 is the result of careful research that created a successful innovative product that combines several types of resins, solvents and co-polymers of different natures. The main feature of CC WSS10, besides being an excellent anti-dust product, is that the effect to the all surface as uniform waterproofing .

MAIN APPLICATION

CC WSS10 is normally used as a sealer to bring back the original beauty and keep the initial protection of all concrete surfaces that the passage of time makes dull and to provide protection against external agents. This sealer is widely used on industrial floors, such as dust and stain resistant floors, chemical resistance .

TIPS FOR USING

CC WSS10 is one-component and is therefore ready for use. CC WSS10 is applied using an airless pump or roller in two coats.

CC WSS10 should not be applied or treated when it is raining (without adequate coverage) or when the temperature is below °5C. If the surface is too wet or there is water, this can lead to the formation of white spots - these can be removed with common solvents. The resin is fully cured in 7 days.

CONSUMPTION

Depending on the degree of finish of the floor and the method used for the preparation (roller or airless), a 20L tin can protect more than 80m²; during particularly hot days, it is advisable to spread the resin in the early morning, with a roller if possible. The extreme heat can increase the resin consumption considerably.

PACKAGING

CC WSS10 is supplied in 20 L gallon.

Shelf life

Original Sealed container has a shelf life of 12 months if stored in the right conditions

FIRE

CC WSS10 is flammable.



CHARACTERISTICS

Appearance Transparent Liquid
Density 1 ± 0.015
Reduction in water absorption 100 %

STORAGE

The containers should be stored in a dry and windless place, with temperatures not lower than °5+C. CCC ensures that the products used for production are exempt from any type of defect. The product, if stored properly, is guaranteed for 12 months.

PRECAUTIONS

The product is flammable; do not smoke when using and applying the resin on hot surfaces. It should be stored in a dry and ventilated place. Avoid contact with the skin, mucous membranes, eyes, etc. In case of accidental contact, wash thoroughly with soap and water and seek medical advice. It is recommended to use masks and gloves. In closed rooms, provide good ventilation and avoid inhalation of fumes.